

ROLL-X® Multipurpose Applicator 400/175 GO



KEY FEATURES

- Manual height adjustment 800-1 000mm / 2ft. 7in - 3ft. 3in.
- Adjustable side trays
- Metal side lines used for trimming
- Fast assembly and installation

ROLL-X® GO is a brand new product and gives you access to the superior production method provided by the Flatbed Applicator technique. The machine can either be shipped in modules to reduce shipping cost and gives you the possibility to fit through a standard door, or be delivered fully assembled. The assembling is fast and easy and you will start making money in no time! Possible to retrofit LED, Gas damper for tilt function and Fabric pocket on short side.



ROLL-X
MULTIPURPOSE APPLICATOR

info@roll-x.se
roll-x.se
+46 54 770 70 00

MODEL NAME	ROLL-X® 400/175 GO
Model type	Go
Part no.	10565
Bed length	4 000 mm / 13ft. 1in.
Bed width	1 750 mm / 5ft. 9in.
Length of working area	3 600 mm / 11ft. 10in.
Width of working area/roller width	1 650 mm / 5ft. 5in.
Overall width incl. Glide beam	1 940 mm / 6ft. 4in.
Max. thickness of substrate	85 mm / 3 2/5in.
Work height flatbed	800-1 000mm / 2ft. 7in - 3ft. 3in.
Bed surface	Tempered glass + Cutting mat
Power Supply	230V/50Hz (10A) / 120V/60Hz 15A)
Required air pressure	4-6 bar / 58-87 psi
Weight	650 kg/ 1 433 lb
Packing weight, total	720 kg/ 1 587 lb
Packing dimension, delivered in parts	4 100 x 1 160 x 2 100 mm / 13ft 5 in. x 3ft. 9in. x 6ft. 10in.
Packing dimension, delivered assembled	4 100 x 2 000 x 1 600 mm / 13ft 5 in. x 6ft 7in. x 5ft 3in.
Casters	8
Warranty	2 years
Owner's Manual	yes (en)
Roll holder for Glide Beam	yes
Roll holder for bed end	yes
Side trays, adjustable	yes
Roll cradle, 1300mm / 4ft 3in.	option
Illumination	option
Flatbed tilt, gas dampers	option
Long life compressor	option
Fabric pocket, short side	option
Assembled at delivery	option